CODE WORKS OF COMMERCE PATEST AND TRADES AND TRADES AND THE TEMPORARY STREET NUMBER (KEV 10-96) ~ TRANSMITTAL LETTER TO THE UNITED STREET PCT/PTO 12 NOV 1997 DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371 INTERNATIONAL FILING DATE INTERNATIONAL APPLICATION NO. PRIORITY DATE CLAIMED 10 MAY 1996 MAY PCT/GB 96/01124 TITLE OF INVENTION BUILDING COMPONENT APPLICANT(S) FOR DO/EO/US SCHOFIELD, Frederick Andrew Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information: This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1). A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date. A copy of the International Application as filed (35 U.S.C. 371(c)(2)) a. 🔯 is transmitted herewith (required only if not transmitted by the International Bureau). has been transmitted by the International Bureau. is not required, as the application was filed in the United States Receiving Office (RO/US). A translation of the International Application into English (35 U.S.C. 371(c)(2)). Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) are transmitted herewith (required only if not transmitted by the International Bureau). have been transmitted by the International Bureau have not been made; however, the time limit for making such amendments has NOT expired. have not been made and will not be made. A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). An oath or declaration of the inventor(s) (35 U.S.C. 371(e)(4)). A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)). Items 11. to 16. below concern document(s) or information included: An Information Disclosure Statement under 37 CFR 1.97 and 1.98. An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 13. Txx A FIRST preliminary amendment. A SECOND or SUBSEQUENT preliminary amendment. A substitute specification. A change of power of attorney and/or address letter. Other items or information: Transmittal sheets in duplicate w/fees charged to Dep. Acct. 07-2100 Copy of WO/96/35848 based on PCT/GB 96/01124 with 7 sheets drawings Preliminary Amendment International Search Report w/13 copies (FR A 2654137, EP A 354084, DP A 356297, EP A 373019, FR A 1119335, FR A1140555, FR A 2559187, DE B 116997, FR A 251131, FR A 2619843 , GB A 434730, AT B 395333, FR A 2698394) Declaration not enclosed at this time, will be filed later.

	NO (if known, see 17 CFR 1.5)	INTERNATIONAL APPLICATION NO. ,	Mark the thing has the		and and
		PCT/GB 96/01124	, r	ATTORNEY'S DOCK	ET NUMBER
The following fees are submitted:				CALCULATIONS	PTO USE ONLY
BASIC NATIONAL FEE (37 CFR 1.492 (n) (1) - (5)): Search Report has been prepared by the EPO or JPO					
			\$910.00	:930:00	
·····	ional preliminary examination	on fee paid to USPTO (37 CFR	\$700.00	1	
No inter but inter	national preliminary examina nucional search fee paid to U	ntion fee pnid to USPTO (37 CF SPTO (37 CFR 1.445(n)(2))	R 1.482) \$770.00		· .
Neither Internati	international preliminary exa onal search fee (37 CFR 1.44	mination fee (37 CFR 1.482) no (5(a)(2)) paid to USPTO	\$1040.00		
Internati and all c	onal preliminary examinatio		•		
		OPRIATE BASIC FEE A		\$ 930.00	
Surcharge of months from	\$130.00 for furnishing the or the earliest claimed priority o	th or declaration later than late (37 CFR 1.492(c)).	20	\$ 130.00	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	<u> </u>	
Total claims	- 20	=	X \$22.00	\$	
Independent cla			X \$80.00	\$	
MULTIPLE	DEPENDENT CLAIM(S) (if ap		+ \$260.00	\$	
		L OF ABOVE CALCULA		\$	
Reduction of must also by	1/2 for filing by small entity, filed (Note 37 CFR 1.9, 1.27,	if applicable. Verified Small E 1.28).	intity Statement	\$	
		SUI	BTOTAL =	\$ 1060.00	
Processing fe months from	e of \$130.00 for furnishing the earliest claimed priority of	ne English translation later than late (37 CFR 1.492(1)).	20 30	\$	
		TOTAL NATIO	NAL-FEE =	\$ 1060.00	
Ree for record	ling the enclosed assignment by an appropriate cover shee	(37 CFR 1.21(h)). The assignment (37 CFR 3.28, 3.31). \$40.00 g	nent must be per property	\$	
		TOTAL FEES EN	CLOSED =	\$ 1060.00	
				Amount to be:	\$
		4		refunded charged	\$
				Charged	
п. [_] Хс	neck in the amount of 3	to cover the ab	ove fees is enclose	d	**
b. 🔯 Plea Ad	nse charge my Deposit Accou uplicate copy of this sheet is	ent No. 07-2100 in the enclosed.	re amount of \$	1060.00 to cov	er the above fees.
c. The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 07-2100. A duplicate copy of this sheet is enclosed.					
				ect is enerosed.	
NOTE: W 1.137(n) or	here an appropriate time li (b)) must be filed and gran	mit under 37 CFR 1.494 or 1. ited to restore the application	495 has not been a to pending status.	net, a petition to revi	ve (37 CFR
SEND ALL CO	NURESPONDENCE TO:	•		1/1/1	2
	Greigg		1	5//	
727-23rd	Street South, Ste.	220 .	SIZANAIS	URE:	
Arlingto	n, VA 22202		RON	ALD E. GREIGG	
Telephon	e: (703) 892-0300		знами	· · · · · · · · · · · · · · · · · · ·	
<u>F</u>	(100) 002 0000	;	Reg	. No. 31,517	
			· ·	•	
		•	Dáte	e: November 12,	1997
Form PTO-1390 (R	FV 10 9() 2. (2				

Rec'd PCT/PTO 12 NOV 1997 08/952474

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re patent application of Frederick Andrew Schofield Based on PCT/GB 96/01124 For: BUILDING COMPONENT

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231
Sir:

Prior to examination, please amend the above-identified application as follows:

IN THE SPECIFICATION:

Page 1, after "Building Component" add a new subtitle as follows: --Summary of the Invention--;

line 21, add a new subtitle as follows:

- --Summary of the Invention--.
- Page 2, between lines 20 and 21, add a new subtitle as follows:
 - --Brief Description of the Drawings --
- Page 3, between lines 13 and 14, add a new subtitle as follows:
 - --Detailed Description of the Invention --

IN THE CLAIMS:

Please cancel claims 1-17 and rewrite as new claims 18-37 herein:

--18. A building component for use in constructing a roof of a building having an inner and outer, double-skinned wall provided with a cavity between said inner and outer skins, said building component comprising:

a block unit having an intermediate capping portion, an outer overhang portion extending downwardly at right angles to the capping portion and an inner leg portion extending downwardly at right angles to the capping portion,

the overhang portion includes an outer face that serves as a barge/fascia board, an under face that serves as a soffit and an inner face,

the capping portion is shaped with a flat top face that extends from an inner edge to an outer edge and a flat under face which is parallel to the flat top face and which extends from the inner face of the overhang portion to an oppositely facing outer face of the inner leg portion,

the shape of the capping portion enables the cap portion to be positioned over, and straddle the outer skin of said double-skinned wall with the outer overhang portion projecting outwardly beyond the outer skin and the inner face of the overhang portion lying opposite an outside of the outer skin.

- 19. A building component according to claim 18, which includes a batt of insulation material secured to an inner end of the block unit.
- 20. A building component according to claim 18, wherein an inner end of the capping portion is rebated to accommodate a heat insulation batt such that the capping portion and inner leg portion have, at their inner end said insulation batt to abut or nearly abut the outside of the inner skin of the double-skinned wall.
- 21. A building component according to claim 18, wherein a marked or recessed panel is provided in the flat top face, and above a flat under face, of the capping portion.
- 22. A building component according to claim 19, wherein a marked or recessed panel is provided in the flat top face, and above a flat under face, of the capping portion.
- 23. A building component according to claim 20, wherein a marked or recessed panel is provided in the flat top face, and above a flat under face, of the capping portion.
- 24. A building component according to claim 18, wherein the under face of the overhang portion serving as a soffit has an outer edge and wherein a drip channel is provided in the under face of the overhang portion adjacent to said outer edge.

- 25. A building component according to claim 19, wherein the under face of the overhang portion serving as a soffit has an outer edge and wherein a drip channel is provided in the under face of the overhang portion adjacent to said outer edge.
- 26. A building component according to claim 20, wherein the under face of the overhang portion serving as a soffit has an outer edge and wherein a drip channel is provided in the under face of the overhang portion adjacent to said outer edge.
- 27. A building component according to claim 18, wherein the capping portion is of equal weight to, or heavier than, the overhang portion to counterbalance or overbalance inwardly the block unit when laid on the outer skin of a double-skinned wall, said overhang portion being hollow, or having multi-cavities therein or being cellular.
- 28. A building component according to claim 19, wherein the capping portion is of equal weight to, or heavier than, the overhang portion to counterbalance or overbalance inwardly the block unit when laid on the outer skin of a double-skinned wall, said overhang portion being hollow, or having multi-cavities therein or being cellular.
- 29. A building component according to claim 20, wherein the capping portion is of equal weight to, or heavier than, the overhang portion to counterbalance or overbalance inwardly the block unit when laid on the outer skin of a double-skinned wall,

said overhang portion being hollow, or having multi-cavities therein or being cellular.

- 30. A building component according to claim 18, wherein the block unit made of any durable material.
- 31. A building component according to claim 30, wherein the durable material is a cementitious material.
- 32. A building component according to claim 18, wherein the capping portion is of equal weight to, or heavier than, the overhang portion to counterbalance or overbalance inwardly the block unit when laid on the outer skin of the double-skinned wall, and wherein the block unit is cast from two cementitious mixtures, one containing a stone aggregate in respect of the capping portion and the other containing a lightweight aggregate in respect of the overhang portion which is solid.
- 33. A building component according to claim 30, wherein the block unit is moulded in a manner in which the overhang under face serving as a soffit and/or overhang outer face serving as a fascia/barge board is/are provided with a wood grain or other ornamental effect.
- 34. A building component according to claim 30, wherein the cementitious material has a mat or fibre reinforcement of synthetic material.

- 35. A roof of a building having a double-skinned wall provided with a cavity between its inner and outer skins and comprising a building component according to claim 18, wherein the block unit is laid in side-by-side relationship with others of its kind as a course at the top of the wall.
- 36. A building component having a single-skinned wall, said building component comprising:

a block unit having an intermediate capping portion, an outer overhang portion extending downwardly at right angles to the capping portion and an inner leg portion extending downwardly at right angles to the capping portion,

the overhang portion having an outer face that serves as a barge/fascia board, an under face that serves as a soffit and an inner face,

the capping portion being shaped with a flat top face extending from an inner edge to an outer edge and a flat under face which is parallel to the flat top face and which extends from the inner face of the overhang portion to an oppositely facing outer face of the inner leg portion.

the shape of the capping portion enabling said capping portion to be positioned over, and straddle the wall with the over overhang portion projecting outwardly beyond the wall and the inner face of the overhang portion lying opposite the outside of the wall.

37. A roof of a building having a single-skinned wall and comprising a building component according to claim 36, wherein

the block unit is laid in side-by-side relationship with others of its kind as a course at the top of the wall.

IN THE ABSTRACT:

Please substitute the ABSTRACT attached hereto for the abstract as originally filed with the application.

REMARKS

This Preliminary Amendment is submitted to more clearly set forth and claim the invention.

Consideration and allowance of the claims are courteously solicited.

Respectfully submitted,

Ronald E. Greigg Reg. No. 31,517

Attorney for Applicant

Suite 220 727-23rd St. South Arlington, Virginia 22202

Telephone: (703) 892-0300

REG/MLC/lh

Rec'd PCT/PTO 12 NOV 1997

WO 96/35848

10

15

20

PCT/GB96/01124

08/952474

BUILDING COMPONENT

This invention relates to a building component for use in constructing a roof for a building primarily, but not only, a building constructed having a "double skin" outer wall(s) particularly, but not necessarily, having a cavity between said skins, the cavity normally being filled or substantially so with an insulation material. A requirement of building regulations currently in force is the capping or closing-off of the top of such cavity. This capping operation is normally achieved by fabrication on site using a board of natural or synthetic material in the same, a preceding or a succeeding operation including a gable wall overhang, a barge board and a soffit. While this invention is primarily concerned with the provision of gable wall overhangs, barge boards and soffits, it is also applicable to the provision of front/rear wall overhangs, fascia boards and soffits. Heretofore, overhangs have been constructed of timber as have barge boards and soffits which require regular painting maintenance with both barge boards and soffits being susceptible to rot and decay and requiring periodic replacement. Barge boards and soffits have also been provided of synthetic plastics material. While these are beneficial in requiring little maintenance they tend to degrade when exposed to sunlight, due to ultra violet radiation and thermal stresses. These existing building components are disadvantageous and an object of the present invention is to obviate or mitigate these disadvantages.

Accordingly, the present invention is a building component comprising a block unit having a capping portion and an overhang portion, the outer face of

10

15

20

25

the overhang portion being to serve as a barge/fascia board. A lower face of the overhang portion beneficially serves as a soffit.

The block unit is desirably for use with others of its kind in being laid side-by-side as a course on top of a wall. Alternatively, a multi-block unit may be provided of desired length for use with others of its kind. The capping portion of the block unit is of tile shape, in a first embodiment, to be positioned over a double-skinned wall and, in a second embodiment, is shaped to be positioned over and straddle the outer skin of the wall. In both embodiments, the overhang portion projects outwardly beyond the wall.

The capping portion is preferably of equal weight to or heavier than the overhang portion to counterbalance or overbalance inwardly the block unit when laid on a wall or the outer skin thereof.

Preferably, the block unit is made of any durable material, for example cementitious material. The overhang portion is beneficially hollow or may have multi-cavities therein, or may be cellular. The block unit may alternatively be cast from two cementitious mixtures, one containing a stone aggregate in respect of the capping portion, and the other containing a light-weight aggregate in respect of the overhang portion which is solid.

Embodiments of the present invention will now be described, by way of example, with reference to the accompanying drawings, in which:-

Fig. 1 is a perspective view of a part of a top and one gable of a building showing a roof support structure with a gable overhang, a barge board and a soffit constructed conventionally;

Fig. 2A is a perspective view of a part of a top and one end of a building showing a roof support structure with a course of block units according to a first embodiment of the present invention; overlying the top of a gable wall;

15

20

25

Fig. 2B is a perspective view of a part of a top and one end of a building showing a roof support structure with a course of block units according to a second embodiment, overlying both the top of a gable wall and a front wall;

Figs. 3A and 3B are similar perspective views of a block unit according to a first embodiment showing different shaped hollow configurations provided in an overhang portion thereof;

Figs. 4A and 4B are respectively, a perspective view and a side elevational view of a modified block unit according to the first embodiment;

Figs. 5A and 5B are respectively, a perspective view and a side elevational view of a block unit according to a second embodiment; and

Figs. 6A and 6B are respectively, a perspective view and a side elevational view of a modified block unit according to a second embodiment having a batt of insulation material secured to the inner end of the block unit.

Referring to the drawings, a building component comprises a block unit 8, 8' having a capping portion 10 /10' and an overhang portion 12 with the outer face of portion 12 serving as a barge or fascia board 14A and a lower face as a soffit 14B.

The block unit 8, 8' is for use with others of its kind in being laid side-by-side as a course on top of a double-skinned wall 16 with the capping portion 10 thereon and the overhang portion 12 projecting outwardly beyond the outer skin of the wall 16.

The capping portion 10 is of equal weight to or heavier than the overhang portion 12 to counterbalance or overbalance inwardly the block unit 8, 8' when laid on a gable wall 16.

The block unit 8, 8' is made of any durable material, for example cementitious material, and can be coloured to suit a particular colour scheme for the rest of the normally painted or coloured parts of a building, for example

10

15

20

25

window frames, guttering or doors. The overhang portion 12 is hollow as shown in Figs. 3A or 3B, 4A or 4B, 5A or 5B, 6A or 6B with a cylindrical tubular formed passage as shown in Fig. 3A or square tubular formed passage as shown in Figs. 3B, 4A, 4B, 5A, 5B, 6A and 6B. Corner or end block units 18 are provided to terminate a course of block units 8, 8' as shown in Figs. 2A and 2B laid on top of the gable wall or front wall 17 in the same manner as conventional bricks or blocks are laid using mortar. An apex 20 may be formed by providing mitre sides to the block units 8, 8' to be abutting at the vertex of the wall. The top surfaces of the block units 8, 8' are flush with the top surfaces of a series of rafters 22 on the gable wall which rafters 22 together provide a roof support structure for a tiled or slated roof including battens and felt/underlay covering.

The outer face of the overhang portions 12 when being moulded may be provided with a wood grain or other ornamental/decorative effect.

A gable overhang and barge board when formed in the manner described above is beneficial over the existing provision for such and requires little or no maintenance.

In a first embodiment, the capping portion 10 of the block unit 8 overlies both skins and closes off the cavity between both skins in the gable wall 16.

In a second embodiment, the capping portion 10' of the block unit 8' overlies horizontally the outer skin of any outer wall and terminates with a downwardly extending leg portion 9 at right angles thereto, the capping portion 10' straddling the outer skin with leg portion 9 closing off the top of the cavity between the double skins of the wall.

Although the invention has been described in connection with pitched gable walls, the building component can equally be used with gable walls 16 of

20

25

flat-roofed structures and with front and rear walls 17 of pitched gable or flat-roofed structures.

As shown in Figs. 4A and 4B, the modified block unit of the first embodiment is provided with a drip channel 24 adjacent to the outer edge of soffit 14B, and a marked or recessed panel 26 is provided in the top face of the capping portion 10 as an indicator for the positioning of a restraining element in the form of a wooden batten (not shown) or the like forming part of a roof structure.

As shown in Figs 5A and 5B, 6A and 6B, the block unit and modified block unit of the second embodiment is provided with a drip channel 24 adjacent to the outer edge of soffit 14B, and a marked or recessed panel 26 is provided in the top face of the capping portion 10 as an indicator for the positioning of a restraining element in the form of a wooden batten (not shown) or the like forming part of a roof structure. The panel 26 when in a recessed form can have a secondary use as a collector of any rain or other water which penetrates between the roof structure and block units.

In a modification of the first embodiment, a multi-block unit is provided of a desired length equal to and to locate between a formed apex unit and a corner or end block unit in each gable wall. Such length units may also be used in multiples along front or rear walls between corner or end block units.

In the manufacture of the block units, the cementious mixtures can have a mat or fibre reinforcement of synthetic material.

In a first modification of both embodiments, the overhang portion is provided with multi-cavities/passages, normally axially parallel to each other, or is of a cellular structure.

In a second modification of both embodiments, the block unit may be cast from two cementitious mixtures, one containing a stone aggregate in

respect of the capping portion and the other containing a light-weight aggregate, for example pumice, perlite (RTM) or expanded polystyrene, in respect of the overhang portion.

In a modification of the second embodiment as shown in Figs. 6A and 6B, the inner end of the capping portion of the block unit is rebated to accommodate a heat insulation batt 28, namely the capping portion 10' and leg portion 9 have at their inner end a heat insulation batt 28 to abut or nearly abut against the outside of the inner skin of the wall.

Variations and other modifications can be made without departing from the scope of the invention described above and as claimed hereinafter.



- I -

CLAIMS

- A building component for use in constructing a roof of a building having a double-skinned wall provided with a cavity between its inner and outer skins, said building component comprising a block unit (8') having an intermediate capping portion (10'),
 an outer overhang portion (12) extending downwardly at right angles to the capping portion (10') and an inner leg portion (9) extending downwardly at right angles to the capping portion (10'), the overhang portion having an outer face serving as a barge/fascia board (14A), an under face serving as a soffit (14B) and an inner face, the capping portion (10') being shaped with a flat top face extending from its inner edge to its outer edge and a flat under face which is parallel to the flat top face and which extends from the inner face of the overhang portion (12) to an oppositely facing outer face of the inner leg portion (9), the shape of the capping portion (10') enabling it to be positioned over, and straddle, the outer skin of a double-skinned wall (17) with the outer overhang portion (12) projecting outwardly beyond the outer skin and the inner face of the overhang portion (12) lying opposite the outside of the outer skin.
 - 2. A building component as claimed in claim 1 and including a batt of insulation material (28) secured to an inner end of the block unit (8').
 - 3. A building component as claimed in claim 1, wherein the inner end of the capping portion (10') is rebated to accommodate a heat insulation batt (28) such that the capping
 5 portion (10') and leg portion (9) have, at their inner end, said insulation batt (28) to abut or nearly abut the outside of the inner skin of the double-skinned wall (17).
 - 4. A building component as claimed in any of claims 1 to 3, wherein a marked or recessed panel 26 is provided in the flat top face, and above the flat under face, of the capping portion (10').
- 10 5. A building component as claimed in any one of claims 1 to 4, wherein the under face of the overhang portion (12) serving as a soffit (14A) has an outer edge and wherein a drip channel (24) is provided in the under face of the overhang portion (12) adjacent to

its said outer edge.

- 6. A building component as claimed in any one of claims 1 to 5, wherein the capping portion (10') is of equal weight to, or heavier than, the overhang portion (12) to counterbalance or overbalance inwardly the block unit (8') when laid on the outer skin of a double skinned wall (17), said overhang portion (12) being hollow, or having multi-cavities therein or being cellular.
 - 7. A building component as claimed in any one of claims 1 to 5, wherein the block unit (8') is made of any durable material.
- 8. A building component as claimed in claim 7, wherein the durable material is a 10 cementitious material.
- 9. A building component as claimed in any one of claims 1 to 5, wherein the capping portion (10') is of equal weight to, or heavier than, the overhang portion (12) to counterbalance or overbalance inwardly the block unit (8') when laid on the outer skin of a double skinned wall (17), and wherein the block unit (8') is cast from two cementitious mixtures, one containing a stone aggregate in respect of the capping portion (10') and the other containing a lightweight aggregate in respect of the overhang portion (12) which is solid.
- 10. A building component as claimed in claim 7 or 8, wherein the block unit (8') is moulded in a manner in which the overhang under face serving as a soffit (14B) and/or overhang outer face serving as a fascia/barge board (14A) is/are provided with a wood grain or other ornamental effect.
 - 11. A building component as claimed in claim 7 to 10, wherein the cementitious material has a mat or fibre reinforcement of synthetic material.
- 12. A building component for use in constructing a roof of a building having a double-25 skinned wall provided with a cavity between its inner and outer skins, substantially as

- 3 -

hereinbefore described with reference to Figs 5A and 5B of the accompanying drawings.


- 13. A building component for use in constructing a roof of a building having a double-skinned wall provided with a cavity between its inner and outer skins, substantially as hereinbefore described with reference to Figs. 6A and 6B of the accompanying drawings.
- 14. A roof of a building having a double-skinned wall (17) provided with a cavity between its inner and outer skins and comprising a building component as claimed in any one of claims 1 to 13, wherein the block unit (8') is laid in side-by-side relationship with others of its kind as a course at the top of the wall (17).
 - 15. A roof of a building having a double-skinned wall provided with a cavity between its inner and outer skins, substantially as hereinbefore described with reference to Fig. 2A of the accompanying drawings.
- 16. A roof of a building having a double-skinned wall provided with a cavity between
 15 its inner and outer skins, substantially as hereinbefore described with reference to Fig.
 2B of the accompanying drawings.
 - 17. A building component as claimed in Claim 1 when used on a single-skinned wall.

ABSTRACT

A building component comprising a block unit having a capping portion and an overhang portion with the outer face of which serving as a barge/fascia board. A lower face of the overhang portion serves as a soffit. The block unit is for use with others of its kind in being laid side-by-side as a course on top of a gable wall or front/rear wall.


PCT/GB96/01124

1/7



PCT/GB96/01124


2/7




The state of the s


PCT/GB96/01124


3/7






of the state of the same with the






SUBSTITUTE SHEET (RULE 26)


PCT/GB96/01124






SUBSTITUTE SHEET (RULE 26)

PCT/GB96/01124





SUBSTITUTE SHEET (RULE 26)

Docket No.

Declaration and Power of Attorney For Patent Application

English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

which a patent is	sought on the invention en	titled		
	BUILDING COM	PONENT		
the specification of	f which			
(check one)				
is attached he	reto.			
☑ was filed on	10 MAY 1996	as United States Application N	o, or PCT in	ntemational
	mahar PCT/CW 06/01174			
and was amer				
	-	(if applicable)		
	I have reviewed and unders, as amended by any ame	rstand the contents of the above endment referred to above.	identified s	pecification,
		ited States Patent and Trademai as defined in Title 37, Code o		
Section 365(b) of any PCT Internat States, listed belo- patent or inventor	any foreign application(s) ional application which de w and have also identified	er Title 35, United States Code, for patent or inventor's certificate esignated at least one country below, by checking the box, any tional application having a filing	e, or Sectio other than foreign ap	n 365(a) of the United plication for
Prior Foreign Appli	cation(s)		Priority	Claimed
05 09 530.3	Great Britain	11 May 1995	Ď	₫
(Number) 96 00 197.9	(Country) Great Britain	(Day/Month/Year Filed) 05 January 1996	0	S
(Number)	(Country)	(Day/Month/Year Fited)		
(Number)	(Country)	(Day/Month/Year Filed)	Ĺ	Ĺ

application(s) listed below:		
(Application Serial No.)	(Filing Date)	_
(Application Serial No.)	(Filing Date)	
(Application Serial No.)	(Filing Date)	-
nsofar as the subject matter of ea Inited States or PCT International J.S.C. Section 112. Tacknowledge Office all information known to me	ach of the claims of this ap application in the manner- the duty to disclose to the to be material to patenta ble between the filing date o	g the United States, listed below and, plication is not disclosed in the prior provided by the first paragraph of 35 United States Patent and Trademark bility as defined in Title 37, C. F. R., f the prior application and the national
	(Filing Data)	(Status)
(Application Serial No.)	(Filing Date)	(patented, pending, abandoned)
(Application Serial No.) (Application Serial No.)	(Filing Date)	(patented, pending, abandoned) (Status) (patented, pending, abandoned)
· · · · · · · · · · · · · · · · · · ·		(Status)
(Application Serial No.) (Application Serial No.) hereby declare that all statementatements made on information and were made with the knowledge that ine or imprisonment, or both, under	(Filing Date) (Filing Date) Ints made herein of my own of the delief are believed to be for the twillful false statements and the section 1001 of Title 18	(Status) (patented, pending, abandoned) (Status)
(Application Serial No.) (Application Serial No.) hereby declare that all statementatements made on information and were made with the knowledge that the or imprisonment, or both, under the willful false statements may	(Filing Date) (Filing Date) Ints made herein of my own of the delief are believed to be for the twillful false statements and the section 1001 of Title 18	(Status) (patented, pending, abandoned) (Status) (patented, pending, abandoned) on knowledge are true and that all ue; and further that these statements of the like so made are punishable by of the United States Code and that

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Edwin E. Greigg - Reg. No. 15,785 Ronald E. Greigg - Reg. No. 31,517

CUSTOMER # 02119	
Send Correspondence to Royald E. Greigg	-
Two Circline Place	
5763 Leechurg Pike #600	
Falls Church, VA 22041	
Direct Telephone Calls to: (name and telephone number,	
tonald E. Greigg - (703) 575-3400/Telephone (703) 892-0303/Facsimile	
Full name of sole or first inventor	
Sole or first inventor's signature	Date
t-11- Schudel	17 TERDUAR
Newtownards, County Down BT23 4RY, Great Britain	12-13-1
Citizenship	
Great Britain	
Post Office Address 3 Crawfordsburn Way	
Newtownards, County Down BT23 4RY, Great Britain	
Full name of second inventor, if any	
Second inventor's signature	Date
Residence	
Citizenship	
Post Office Address	

Page 1 of 2

VERIFIED ST STATUS (3	ATEMENT (DECLA 7 CFR 1.9(f) AND 1.	RATION) (27 (b)) - INJ	CLAYMING SMALL ED DEPENDENT INVENT	OR	Docket No.
Serial No. 08/952,474	Filing		Patent No.		Issue Date
Applicant/ Patentee:	FREDERIC	CK ANDREW	SCHOFFELD		
Invention:	виц	DING COM	PONENT		
for purposes of pa Trademark Office	d inventor, I hereby declaying reduced fees under with regard to the inventionation to be filed here	ir section 41(a tion entitled at	olify as an independent inv and (b) of Title 35, Unite cove and described in:	entor as de ed Stales C	fined in 37 CFR 1.9(c) code, to the Patent and
	lication identified above.				70
	ent identified above.				2
grant, convey or inventor under 37 small business co Each person, cor obligation under c	license, any rights in the CFR 1.9(c) if that personner under 37 CFR 1.9 neem or organization to contract or law to assign, a person, concern or organization to person, concern or organization.	e invention to on had made to (d) or a nonpr which I have grant, convey inization exist	and am under no obligation any person who could not the invention, or to any could off organization under 37 (assigned, granted, convert, or license any rights in the state of the convertion o	ncem which CFR 1.9(e).	would not qualify as a
∐ Each su	ich person, concern or or	ganization is l	isted below.		
*NOTE: S riç	eparate verified stateme ghts to the invention ave	nts are require ming to their s	ed from each named person tatus as small entities (37 (n, concem (CFR 1.27)	or organization having
FULL NAME ADDRESS	tndividual	L) Sn	nall Business Concern		Nonprofit Organization
FULL NAME ADDRESS	individual		nall Business Concern		,,
FULL NAME	Individual		nall Business Concern		Nonprofit Organization
FULL NAME ADDRESS	☐ Individual		mall Business Concern		Nonprofit Organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF INVENTOR Frederick A	ndrew SCHOFIELD		
SIGNATURE OF INVENTOR	I fl Schopele	DATE:	12 FEBRUAR 199
NAME OF INVENTOR			
SIGNATURE OF INVENTOR		DATE:	
•			
NAME OF INVENTOR			
SIGNATURE OF INVENTOR		DATE:	
NAME OF INVENTOR			
SIGNATURE OF INVENTOR		DATE:	
NAME OF INVENTOR			
SIGNATURE OF INVENTOR		DATE:	
			·
SIGNATURE OF INVENTOR		DATE:	
NAME OF INVENTOR			
SIGNATURE OF INVENTOR		DATE:	
		•	
SIGNATURE OF INVENTOR		DATE:	,
ALLAND OF BUILDING			
SIGNATURE OF INVENTOR		DATE:	
NAME OF INVENTOR			
SIGNATURE OF INVENTOR		DATE:	
SIGNATURE OF INVENTOR		DATE:	